



EU Type Examination Certificate CML 15ATEX1040X Issue 9

- 1 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- 2 Equipment **Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Posi Adaptors, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors**
- 3 Manufacturer **CCG Cable Terminations PTY LTD**
- 4 Address **33-37 Forge Road,
Spartan Industrial Area,
Kempton Park 1619,
South Africa**
- 5 The equipment is specified in the description of this certificate and the documents to which it refers.
- 6 Eurofins CML B.V., Chamber of Commerce No 67386717, Koopvaardijweg 32, 4906CV Oosterhout, The Netherlands, Notified Body Number 2776, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 12.

- 7 If an 'X' suffix appears after the certificate number, it indicates that the equipment is subject to conditions of safe use (affecting correct installation or safe use). These are specified in Section 14.
- 8 This EU Type Examination certificate relates only to the design and construction of the specified equipment or component. Further requirements of Directive 2014/34/EU Article 13 apply to the manufacture of the equipment or component and are separately certified.
- 9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:

EN IEC 60079-0:2018

EN 60079-1:2014

EN IEC 60079-7:2015+A1:2018

EN 60079-31:2014

- 10 The equipment shall be marked with the following:

II 2G 1D

Ex db IIC Gb
Ex eb IIC Gb
Ex ta IIIC Da
IP66/67/68 (2m cont)

(All product ranges except plastic blanking plugs)

II 2G 1D

Ex eb IIC Gb
Ex ta IIIC Da
IP66/67/68 (2m cont)

(Plastic blanking plugs)

I M2

Ex db I Mb
Ex eb I Mb
IP66/67/68 (2m cont)

(All product ranges except plastic blanking plugs, insulated and Posi adaptors, and any aluminium product. See Specific Conditions of Use)

(Above is the full marking that applies to all the devices, due to limited space on the product, a summarised version appears on the actual devices)



This certificate shall only be copied in its entirety and without change

www.CMLEX.com



11 Description

The Range of Threaded Adaptors, Reducers, Unions, Couplers, Insulated Adaptors, Insulated Reducers, Posi Adaptors, Adjustable Elbows, 'T' or 'Y' Adaptors, Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors and Blanking Plugs are designed for inserting into enclosures having threaded entries, as appropriate for the type of protection.

The following details the Model Nomenclature:

Product Name	Model Nomenclature	Product Name	Model Nomenclature
Threaded Adaptors	AGZZZGYYYE	Threaded Blanking Plugs	PFGZZZER
Integral Earth Adaptors	AGZZZGYYYE - IE	Plastic blanking plugs	3527ZZZ
Threaded Reducers	RGZZZGYYYE		
Threaded Unions	UGZZZGYYYE		
Threaded Couplers	CGZZZGYYYE		
Insulated Adaptors	AGZZZGYYYE -INSA		
Insulated Reducers	RGZZZGYYYE-INSA		
Posi Adaptors	PAGZZZGYYYE		
Adjustable Elbow	AELBGZZGYYYE		
Adjustable 'T' Adaptor	ATGZZZGYYYE		
Adjustable 'Y' Adaptor	AYGZZZGYYYE		
Swivel Adaptor	SAGZZZGYYYE		
Swivel Coupler	SCGZZZGYYYE		
Swivel Elbow Adaptor	SELBGZZGYYYE		
Swivel 45° Adaptor	S45GZZZGYYYE		
Swivel Barrier Adaptor	SBAGZZZGYYYE		
Swivel Barrier Coupler	SBCGZZZGYYYE		
Swivel Barrier Elbow Adaptor	SBELBGZZZGYYYE		
Swivel Barrier 45° Adaptor	SB45GZZZGYYYE		
Where:			
A = ADAPTOR		F = TYPE	
R = REDUCER		S = STOPPER	
U = UNION		D = DOME HEAD	
C = COUPLER		H = HEX HEAD	
PA= POSI ADAPTOR		G = THREADFORM	
AELB = ADJUSTABLE ELBOW		M = METRIC	
AT = ADJUSTABLE 'T' ADAPTOR			



AY =	ADJUSTABLE 'Y' ADAPTOR		
SA =	SWIVEL ADAPTOR		
SC =	SWIVEL COUPLER		
SELB =	SWIVEL ELBOW ADAPTOR		
S45 =	SWIVEL 45° ADAPTOR		
SBA =	SWIVEL BARRIER ADAPTOR		
SBC =	SWIVEL BARRIER COUPLER		
SBELB =	SWIVEL BARRIER ELBOW ADAPTOR		
SB45 =	SWIVEL BARRIER 45° ADAPTOR		
G =	THREADFORM	N =	NPT
	M = METRIC	B =	BSPP
	N = NPT	BSPT =	BSPT
	NPSM NPSM	NPSM =	NPSM
	=		
	B = BSPP	P =	PG
	BSPT BSPT	G =	EUROPE G (PARALLEL)
	=		
	P = PG	GK =	GK (TAPER)
	G = EUROPE G (PARALLEL)	R =	R (PARALLEL)
	GK = GK (TAPER)	RK =	RK (TAPER)
	R = R (PARALLEL)	PF =	JAPAN PF (PARALLEL)
	RK = RK (TAPER)	K =	K mpy (TAPER)
	PF = JAPAN PF (PARALLEL)	ET=	ET
	K = K mpy (TAPER)	ZZZ =	THREAD SIZE
	ET= ET	E =	Ex COMPONENT
ZZZ =	MALE THREAD SIZE	R=	HEX ON REVERSE FACE
YYY =	FEMALE THREAD SIZE		
E =	Ex COMPONENT		
IE =	INTEGRAL EARTH		
INSA =	INSULATED		

Where the thread size coding is as follows:

Metric sizes			BSP/NPT/NPSM sizes	
012 = M12	020 = M20	100 = M100	012 = $\frac{1}{2}$ "	034 = $\frac{3}{4}$ "
016 = M16	032 = M32	110 = M110	001 = 1"	114 = $1\frac{1}{4}$ "
025 = M25	050 = M50	120 = M120	112 = $1\frac{1}{2}$ "	002 = 2"
040 = M40	075 = M75	130 = M130	212 = $2\frac{1}{2}$ "	003 = 3"
063 = M63	090 = M90		312 = $3\frac{1}{2}$ "	004 = 4"
080 = M80			005 = 5" (Not BSP)	



For metric threads the pitch is:-

- M75 and smaller has 1.5mm pitch (minimum thread length 12mm) as standard with an optional pitch of 2mm (minimum thread length 16mm)
- M80 and larger has 2 mm pitch (minimum thread length 16mm) as standard with an optional pitch of 1.5mm (minimum thread length 12mm).
- Note: Intermediate metric thread sizes are allowed and use the same format of product and size coding, e.g., 033 = M33

Threaded Adaptors and Reducers

The Range of Threaded Adaptors and Reducers are used to convert a threaded entry from one thread size or type to another. The devices are manufactured from brass (nickel plated), stainless steel, mild steel, aluminium or bronze. A non-metallic washer/gasket may be utilised on all non-tapered threads to ensure IP66/67/68 (2 m cont.) ratings. The devices maintain an IP65 rating with no washer fitted. The size and thread forms are shown in Tables 1 to 4:

Table 1, Metric to Metric

Male (Metric) Size	Female (Metric) Size													
	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	M110	M120	M130
M16	A	A	A											
M20	R	A	A	A										
M25	R	R	A	A	A									
M32	R	R	R	A	A	A								
M40	R	R	R	R	A	A	A							
M50	R	R	R	R	R	A	A	A						
M63	R	R	R	R	R	A	A	A						
M75	R	R	R	R	R	R	A	A	A					
M80	R	R	R	R	R	R	R	A	A	A				
M90	R	R	R	R	R	R	R	R	A	A	A			
M100	R	R	R	R	R	R	R	R	R	A	A	A		
M110	R	R	R	R	R	R	R	R	R	R	A	A	A	
M120	R	R	R	R	R	R	R	R	R	R	R	A	A	
M130	R	R	R	R	R	R	R	R	R	R	R	R	R	A

A = Adaptor, R = Reducer



eurofins



CML 15ATEX1040X
Issue 9

Table 2, Metric to BSP/NPT

Male (Metric) Size	Female (BSP/NPT/NPSM) Size										
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"
M16	A	A									
M20	A/R*	A	A								
M25	R	A/R*	A	A							
M32	R	R	A/R*	A	A						
M40	R	R	R	A/R*	A	A					
M50	R	R	R	R	A/R*	A	A				
M63	R	R	R	R	R	A/R*	A	A			
M75	R	R	R	R	R	R	A/R*	A	A		
M80	R	R	R	R	R	R	A/R*	A	A		
M90	R	R	R	R	R	R	R	A/R*	A		
M100	R	R	R	R	R	R	R	R	A		
M110	R	R	R	R	R	R	R	R	R	A	
M120	R	R	R	R	R	R	R	R	R	R	A
M130	R	R	R	R	R	R	R	R	R	R	A

A = Adaptor, R = Reducer; R* = Metric to NPT reducers only,

* Not BSP

Table 3, BSP/NPT/NPSM to Metric

Male (BSP/NPT/NPSM) Size	Female (Metric) Size													
	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	M110	M120	M130
1/2"	R	A	A	A										
3/4"	R	R	A	A	A									
1"	R	R	R	A	A	A								
1 1/4"	R	R	R	R	A	A	A							
1 1/2"	R	R	R	R	R	A	A	A						
2"	R	R	R	R	R	R	A	A	A					
2 1/2"	R	R	R	R	R	R	R	A	A	A				
3"	R	R	R	R	R	R	R	R	A	A	A			
3 1/2"	R	R	R	R	R	R	R	R	R	A	A			
4"	R	R	R	R	R	R	R	R	R	R	A	A		
5"	R	R	R	R	R	R	R	R	R	R	R	A	A	

A = Adaptor, R = Reducer

This certificate shall only be copied
in its entirety and without change



Table 4, BSP to BSP, BSP to NPT, BSP to NPSM, NPT to BSP, NPT to NPT, NPT to NPSM and NPSM to NPSM

Male (BSP/NPT/NPSM) Size	Female (BSP/NPT/NPSM) Size									
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	A	A	A							
3/4"	R	A	A	A						
1"	R	R	A	A	A					
1 1/4"	R	R	R	A	A	A				
1 1/2"	R	R	R	R	A	A	A			
2"	R	R	R	R	R	A	A	A		
2 1/2"	R	R	R	R	R	R	A	A	A	
3"	R	R	R	R	R	R	R	A	A	A
3 1/2"	R	R	R	R	R	R	R	A	A	
4"	R	R	R	R	R	R	R	R	R	A

A = Adaptor, R = Reducer

Integral Earth Adaptors

Integral Earth Adaptors have identical male and female threads and are fitted with an earth stud to provide and earth connection for the cable gland fitted to them. The devices are manufactured from brass (nickel plated), stainless steel, mild steel, aluminium or bronze. A non-metallic washer/gasket may be utilised on all non-tapered threads to ensure IP66/67/68 (2 m cont.) ratings. The devices maintain an IP65 rating with no washer fitted. The size and thread forms are M20 to M100 (metric) and 1/2" to 4" NPT.

Threaded Couplings/Unions

The Range of Threaded Couplings and Unions is designed to provide an intermediate part for fitting between certified cable glands and threaded entries of the same or different form and/or sizes of threads (Male to male – Couplings and female to female – Unions). The devices are manufactured from brass (nickel plated), stainless steel, aluminium, mild steel or bronze. A non-metallic washer/gasket may be utilised on all non-tapered threads to ensure IP66/67/68 (2 m cont.) ratings. The devices maintain an IP65 rating with no washer fitted. The size and thread forms are shown in Tables 5 to 10:



eurofins



CML 15ATEX1040X
Issue 9

Table 5, Couplings - Metric to Metric

Male (Metric) Size	Male (Metric) Size													
	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	M110	M120	M130
M16	X													
M20	X	X												
M25	X	X	X											
M32		X	X	X										
M40		X	X	X	X									
M50			X	X	X	X								
M63				X	X	X	X							
M75					X	X	X	X						
M80						X	X	X	X					
M90							X	X	X	X				
M100								X	X	X	X			
M110									X	X	X	X		
M120										X	X	X	X	
M130											X	X	X	X

Table 6, Couplings - BSP to BSP, BSP to NPT, BSP to NPSM, NPT to BSP and NPT to NPT, NPT to NPSM and NPSM to NPSM

Male (BSP/NPT/NPSM) Size	Male (BSP/NPT/NPSM) Size									
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	X									
3/4"	X	X								
1"	X	X	X							
1 1/4"		X	X	X						
1 1/2"		X	X	X	X					
2"			X	X	X	X				
2 1/2"				X	X	X	X			
3"					X	X	X	X		
3 1/2"						X	X	X	X	
4"							X	X	X	X



eurofins



CML 15ATEX1040X
Issue 9

Table 7, Coupling - BSP to Metric, NPSM to Metric and NPT to Metric

Male (BSP/NPT /NPSM) Size	Male (Metric) Size													
	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	M110	M120	M130
1/2"	X	X	X											
3/4"	X	X	X	X	X									
1"	X	X	X	X	X	X								
1 1/4"		X	X	X	X	X	X							
1 1/2"		X	X	X	X	X	X	X						
2"			X	X	X	X	X	X	X					
2 1/2"				X	X	X	X	X	X	X				
3"					X	X	X	X	X	X	X	X	X	X
3 1/2"						X	X	X	X	X	X	X	X	X
4"							X	X	X	X	X	X	X	X

Table 8, Unions - Metric to Metric

Female (Metric) Size	Female (Metric) Size													
	M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	M110	M120	M130
M16	X													
M20	X	X												
M25	X	X	X											
M32	X	X	X	X										
M40	X	X	X	X	X									
M50		X	X	X	X	X								
M63			X	X	X	X	X							
M75				X	X	X	X	X						
M80					X	X	X	X	X					
M90						X	X	X	X	X				
M100							X	X	X	X	X			
M110								X	X	X	X	X		
M120									X	X	X	X	X	
M130										X	X	X	X	



eurofins



CML 15ATEX1040X
Issue 9

Table 9, Unions - BSP to BSP, BSP to NPT, BSP to NPSM, NPT to BSP, NPT to NPT, NPT to NPSM and NPSM to NPSM

Female (BSP/NPT/NPSM) Size	Female (BSP/NPT) Size									
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	X									
3/4"	X	X								
1"	X	X	X							
1 1/4"	X	X	X	X						
1 1/2"	X	X	X	X	X					
2"		X	X	X	X	X				
2 1/2"			X	X	X	X	X			
3"				X	X	X	X	X		
3 1/2"					X	X	X	X	X	
4"						X	X	X	X	X

Table 10, Union - Metric to BSP/NPT/NPSM

Female (Metric) Size	Female (BSP/NPT/NPSM) Size									
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
M16	X	X	X	X						
M20	X	X	X	X	X					
M25	X	X	X	X	X	X				
M32	X	X	X	X	X	X	X			
M40	X	X	X	X	X	X	X	X		
M50		X	X	X	X	X	X	X	X	
M63			X	X	X	X	X	X	X	X
M75				X	X	X	X	X	X	X
M80					X	X	X	X	X	X
M90						X	X	X	X	X
M100							X	X	X	X
M110								X	X	X
M120									X	X
M130										X



Threaded Metallic Blanking Plugs

The Range of Threaded Metallic Blanking Plugs are designed for blanking off threaded entries in enclosures. The devices are manufactured from brass (nickel plated), stainless steel, mild steel, aluminium or bronze. A non-metallic washer/gasket may be utilised on all non-tapered threads to ensure IP66/67/68 (2 m cont.) ratings. The devices maintain an IP65 rating with no washer fitted. The size and thread forms are shown in Table below:

Hex. head		Dome head		Stopper (External Hex. Keyway)		Stopper (Internal. Hex. Keyway)	
Metric	BSP/NPT/ NPSM	Metric	BSP/NPT/ NPSM	Metric	BSP/NPT/ NPSM	Metric	BSP/NPT/ NPSM
M12	-	M12	-	M12	-	M12	-
M16	1/2"	M16	1/2"	M16	1/2"	M16	1/2"
M20	3/4"	M20	3/4"	M20	3/4"	M20	3/4"
M25	1"	M25	1"	M25	1"	M25	1"
M32	1 1/4"	M32	1 1/4"	M32	1 1/4"	M32	1 1/4"
M40	1 1/2"	M40	1 1/2"	M40	1 1/2"	M40	1 1/2"
M50	2"	M50	2"	M50	2"	M50	2"
M63	2 1/2"	M63	2 1/2"	M63	2 1/2"	M63	2 1/2"
M75	3"	M75	3"	M75	3"	M75	3"
M80	3 1/2"	M80	3 1/2"	M80	3 1/2"	M80	3 1/2"
M90	4"	M90	4"	M90	4"	M90	4"
M100	-	M100	-	M100	-	M100	-
M110	-	M110	-	M110	-	M110	-
M120	-	M120	-	M120	-	M120	-
M130	-	M130	-	M130	-	M130	-

Threaded Non-metallic Blanking Plugs

The Range of Threaded Non-metallic Blanking Plugs are designed for inserting into enclosures having metric threaded entries, as appropriate for the type of protection. A sealing gasket is used to maintain the IP rating.

The following sizes are covered by this approval:

M20 x 1.5

M25 x 1.5

M32 x 1.5

M40 x 1.5



Insulated Adaptors

The range of insulated adaptors are manufactured from a hollow cylindrical non-metallic insulated body with two metallic parts on opposite ends for male and female engagement with typically an enclosure and cable gland.

The insulated adaptor provides electrical insulation from one end to the other. The adaptor thread sizes are the same, or equivalent, on both ends, e.g., M16 to M16, or M20 to $\frac{1}{2}$ " NPT. The following sizes are included in the range:

Metric thread from M16 to M130. (A sealing gasket is supplied as standard on the male threaded part to maintain the IP rating.)

NPT threads from $\frac{1}{2}$ " to 4"

The male and female threads do not need to be the same type.

Insulated Reducers

The range of insulated reducers are manufactured from a hollow cylindrical non-metallic insulated body with two metallic parts on opposite ends for male and female engagement with typically an enclosure and cable gland.

The insulated reducer provides electrical insulation from one end to the other. The female thread size on the insulated reducer is always smaller than the male thread size. The following sizes are included in the range:

Metric male threads from M20 to M130 and metric female threads from M16 to M120. (A sealing gasket is supplied as standard on the male threaded part to maintain the IP rating.)

NPT male threads from $\frac{3}{4}$ " to 4" and NPT female threads from $\frac{1}{2}$ " to 3- $\frac{1}{2}$ "

The male and female threads do not need to be the same type.

Posi Adaptors

The Posi adaptor has a brass core with a corrosion-protecting outer skin compression moulded around it. The Posi adaptor also has an earthing stud connected through the corrosion protection (and insulating) skin.

The Posi Adaptor is an adaptor available only in the sizes

MALE THREAD	FEMALE THREAD
M20 x 1.5 – 6g	M20 x 1.5 – 6H
M20 x 1.5 – 6g	M25 x 1.5 – 6H
M25 x 1.5 – 6g	M20 x 1.5 – 6H
M25 x 1.5 – 6g	M25 x 1.5 – 6H



Adjustable Elbow, 'T' and 'Y' Adaptors

The Adjustable Elbow (90°), 'T' and 'Y' Adaptors are manufactured from brass or stainless steel with a male threaded portion at one end. The 90° adaptors have a single female thread, and the 'T' and 'Y' adaptors have two female threads. The 'T' adaptor has its male thread at 90° to each of the female threads and the female threads are at 180° to each other. The 'Y' adaptors have their threads spaced at 120° to each other.

90° adaptors are intended for use where space is limited and there may not be room to fit a gland and cable in the conventional manner. 'T' and 'Y' adaptors are used where two cable glands or a cable gland and another device (e.g. a breather drain plug) need to be fitted to a single entry hole.

The Adjustable 90°, 'T' and 'Y' adaptors are intended for fitting to a threaded hole for Ex db or Ex eb applications or to a plain hole, secured with a locknut, for Ex eb applications. The Adjustable Adaptors allow repositioning to align the cable in the desired direction when the adaptor is fully tightened.

The Adjustable 90°, 'T' and 'Y' Adaptors are available with Metric or BSPP male threads and either metric, NPT, ET, BSPP or BSPT female threads the same size or any size smaller than the male thread.

On the Adjustable 'T' and 'Y' adaptors the female threads do not need to be the same size as each other.

The Adjustable Adaptors are available with thread sizes M20, M25 & M32 or equivalent size in the other thread types.

A non-metallic washer/gasket may be utilised on all non-tapered threads to ensure IP66/67/68 (2 m cont.) ratings. The devices maintain an IP65 rating with no washer fitted.

Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors

The Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors are manufactured from brass, bronze, aluminium or stainless steel with a male threaded portion at one end. They are made in two parts connected together with a nut, and the junction between the two parts forms a serrated flamepath. The Swivel Adaptor, Swivel Elbow and Swivel 45° Adaptors have a single male and a single female thread, and the Swivel Coupler has two male threads.

The Swivel Adaptor or Coupler can be used to connect two pieces of Ex Equipment. The Swivel Elbow and 45° Adaptors are intended for use where space is limited and there may not be room to fit a gland and cable in the conventional manner.

The Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors are intended for fitting to a threaded hole for Ex db or Ex eb applications or to a plain hole, secured with a locknut, for Ex eb applications. The Swivel Elbow / 45° Adaptors allow repositioning to align the cable in the desired direction when the adaptor is fully tightened.

The Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors are available with Metric, NPT, ET, BSPP or BSPT threads the same size or with the female thread any size smaller than the male thread. The Swivel Coupler can also have one male thread smaller than the other.



eurofins



CML 15ATEX1040X
Issue 9

The Swivel Adaptor or Swivel Coupler are available with thread sizes from M20 to M100, or equivalent size in the other thread types. The Swivel Elbow / 45° Adaptors are available with thread sizes from M20 to M63, or equivalent size in the other thread types. The Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors can also be supplied with the male thread size one size larger. For example, a Swivel Elbow Adaptor body size that would normally have M50 male and female threads can also be supplied with an M63 male and an M50 female thread.

A non-metallic washer/gasket may be utilised on all parallel threads to ensure an IP66 rating. The devices maintain an IP65 rating with no washer fitted.

Swivel Barrier Adaptor, Swivel Barrier Coupler and Swivel Barrier Elbow / 45° Adaptors

The Swivel Barrier Adaptor, Swivel Barrier Coupler and Swivel Barrier Elbow / 45° Adaptors are the same basic construction as their equivalent non-barrier versions but additionally have a resin sleeve inside the male thread. The resin sleeve forms a flamepath with its mating part and is filled with 'Quickstop Ex' or 'Vortex' resin to form a barrier around the cable conductors.

Notes

1. All units are rated IP65 for any sealing arrangement. Units with parallel threads shall be used with the supplied washer if an IP rating of IP66/67/68 is required (IP66 for the Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors.) . NPT threads are at least IP65 as standard, but IP68 (2m) (IP66 for the Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors.) can be achieved if one of the following grease types is applied to the NPT thread before fitting:- Renolit Lubrene CA 700, Renolit LC-WP2, Renolit Lubrene LX 220 EP2, Renolit Moly LX 2 or Dow Corning 4 Electrical Compound.
2. RE-FLEX sealing cord can be used as an alternative to a standard sealing gasket to achieve IP66/68 (IP66 for the Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors.). It is intended as a retro-fit solution and must be installed according to the fitting instructions supplied with it.



Variation 1

This variation introduced the following modifications:

- i. The introduction of a Range of Insulated Adaptors

The range of insulated adaptors are manufactured from a hollow cylindrical non-metallic insulated body with two metallic parts on opposite ends for male and female metric engagement with typically an enclosure and gland.

The insulated adaptor provides electrical insulation from one end to the other. The adaptor thread sizes are the same on both ends, e.g., M16 x 1.5 to M16 x 1.5. The following sizes are included in the range:

M16, M20, M25, M32, M40, M50, M63, M75, M80, M90 & M100 (All 1.5 or 2.0 pitch, 6H/6g tolerance).

A sealing gasket is utilised on the male threaded part to maintain the IP rating.

Variation 2

This variation introduced the following modifications:

- i. The introduction of a NPT, BSP, BSPT and NPSM versions of the Insulated Adaptors in the following sizes:
½", ¾", 1", 1 ¼", 1 ½", 2", 2 ½", 3", 3 ½", 4" (NPT, BSP, BSPT or NPSM).
- ii. To include an Insulated Reducer range to provide a reduced female thread size any size smaller than the male.
- iii. The Conditions of Safe Use have been updated to include torque values for non-metric sizes.
- iv. To update the certificate to reference the 2014/34/EU Directive.

Variation 3

This variation introduced the following modifications:

- i. To update to latest edition of all standards.
- ii. The addition of Posi adaptor range.
- iii. Description updated accordingly to include the addition adaptor range.
- iv. Minor changes to description to clarify product ranges.
- v. Minor drawing changes not effecting compliance.

Variation 4

This variation introduced the following modifications:

- i. Following appropriate assessment to demonstrate compliance with the latest technical knowledge, the document previously listed, EN 60079-0:2012+A11:2013, was replaced by EN IEC 60079-0:2018.
- ii. To assess and permit the addition of alternative gasket materials.
- iii. To allow standard adaptors, reducers, unions and couplers to be alternatively manufactured from aluminium (Group II & III only).
- iv. The description and specific conditions of use have been updated accordingly to include the aluminium material option and the alternative gasket materials.
- v. To allow the products to be manufactured with intermediate metric thread sizes.

Variation 5

This variation introduced the following modification:

- i. To allow the increase of the maximum Metric thread sizes from M100 to M130.



Variation 6

This variation introduced the following modifications:

- i. The transfer of the plastic blanking plugs from CML 15ATEX3094X to this certificate.
- ii. To update the certificate format, and where applicable, the description has been updated in accordance with the modifications.
- iii. To update the coding from Ex tb IIIC Db to Ex ta IIIC Da.
- iv. To update EN IEC 60079-7 to the latest edition.
- v. To permit changes to the Specific Conditions of Use.
- vi. To allow the use of the grease for NPT threads to achieve IP68.
- vii. The addition of an Integral Earth Adaptor.
- viii. The addition of the RE-FLEX sealing cord.
- ix. The addition of E.T thread option.
- x. To update the certification drawings with minor corrections.

Variation 7

This variation introduced the following modifications:

- i. The introduction of the Swivel 90°, 'T' and 'Y' Adaptors with the following modifications;
 - a. To update the name of the product from Swivel 90°, 'T' and 'Y' Adaptors to Adjustable Elbow, 'T' and 'Y' Adaptors.
 - b. To update the coding from Ex tb IIIC Db to Ex ta IIIC Da.
 - c. To include ET threads.
 - d. To update EN IEC / IEC 60079-7 to the latest edition.
 - e. To allow the use of the grease for NPT threads to achieve IP68.
 - f. To update the product from a component to equipment.
- ii. The introduction of the Swivel Adaptor, Swivel Coupler, Swivel Elbow / 45° Adaptors
- iii. To update the certificate with the following modifications;
 - a. To update the description as a result of the modifications.
 - b. To permit changes to the conditions of manufacture.
 - c. To permit changes to the specific conditions of use.

Variation 8

This variation introduced the following modifications:

- i. Introduction of the Insulated Reducer.
- ii. Max NPT thread size increased to 5" on NPT to NPT and NPT to Metric or Metric to NPT adaptors and reducers.
- iii. To increase the number of cores in some sizes of barrier swivel products.
- iv. To increase the height of some sizes of adjustable elbow.
- v. The introduction of an M12 thread option on the stopper plugs.
- vi. To update the certification drawings with minor corrections.



12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
0	15 Apr 2015	R517A/00	Issue of Prime Certificate
1	14 Oct 2015	R786A/00	Introduction of Variation 1
2	01 Jun 2016	R1302A/00	Introduction of Variation 2
3	10 Aug 2016	R1347B/00	Introduction of Variation 3
4	16 Sep 2016	-	Addition of IP rating to certificate marking, to remove a redundant Condition of Manufacture and clarify a Condition of Safe Use
5	23 Aug 2019	R12622A/00	Introduction of Variation 4
6	28 Feb 2020	R13063A/00	Introduction of Variation 5
7	26 Jul 2022	R15542A/00	Introduction of Variation 6
8	23 Jun 2023	R16124A/00	Introduction of Variation 7
9	22 Jan 2026	R19188A/00	Introduction of Variation 8

Note: Drawings that describe the equipment or component are listed in the Annex.

13 Conditions of Manufacture

The following conditions are required of the manufacturing process for compliance with the certification.

- i. Insulated and Posi adaptors shall not be marked for Group I applications.
- ii. Products made from aluminium shall not be marked for Group I.
- iii. The products listed in this certificate with intermediate metric entry thread sizes shall be constructed by enlarging the entry thread size of the standard size product immediately below the intermediate thread size. The minimum entry wall thickness and constructional parts utilised (other than the entry thread component) shall not differ from that of the standard size used.

14 Specific Conditions of Use (Special Conditions)

The following conditions relate to safe installation and/or use of the equipment.

General Conditions

- i. To maintain the IP rating, the installer shall ensure that the surface of the enclosure against which the sealing gasket seals is in good condition.
- ii. The sealing arrangement of the gland into the adaptor / reducer shall conform to the gland certification and IP rating requirements (as applicable).
- iii. When supplied with a washer/gasket, the following service temperatures apply:
 - HDPE gasket – Tservice = -60°C to +95°C
 - Nylon gasket – Tservice = -60°C to +100°C
 - PTFE gasket – Tservice = -60°C to +160°C



Conditions for specific products

- i. A service temperature range of -20°C to +95°C shall not be exceeded for the Insulated Adaptor or Insulated Reducer.
- ii. The tightening torque for the glands installed in the insulated adaptors may not exceed:

Thread Size and Form	Tightening torque (Nm)	Thread Size and Form	Tightening torque (Nm)
M16	40	M63 and 2" NPT	115
M20 and 1/2" NPT	40	M75 and 2 1/2" NPT	140
M25 and 3/4" NPT	55	M80	160
M32 and 1" NPT	65	M90 and 3" NPT	180
M40 and 1 1/4" NPT	80	>M90 and >3" NPT	200
M50 and 1 1/2" NPT	100		

Note: NPT size torque values also apply to the equivalent BSP, BSPT and NPSM sizes.

- iii. A service temperature range of -20°C to +95°C (HDPE sealing gasket) or -20°C to +106°C (Nylon sealing gasket) shall not be exceeded for the plastic blanking plug.
- iv. The Swivel Adaptors, Swivel Couplers and Swivel Elbow / 45° Adaptors are only to be used in Group I applications where the risk of mechanical impact is low.
- v. The Swivel Barrier products shall only be used where the temperature is between:
 - Quickstop or Vortex resin type S50 / EPA:
(-50°C and +95°C)
 - Quickstop or Vortex resin type FR/846:
(-60°C and +100°C)

Certificate Annex



Certificate Number CML 15ATEX1040X

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD

The following documents describe the equipment or component defined in this certificate:

Issue 0

Drawing No	Sheets	Rev	Approved date	Title
8055-SG	1 of 1	1	14 Apr 2015	No. "X" CCG Sealing Gasket
AM016M100E MARKING	1 of 1	8	14 Apr 2015	Adaptors-Reducers-Plugs-Couplers and Unions Marking Details
AB012B012E to AB004B004E and RB034B012E to RB004B312E	1 of 1	1	14 Apr 2015	BSP to BSP Adaptors & Reducers Ex
AB012M020E to AB004M100E and RB012M016E to RB004M100E	1 of 1	1	14 Apr 2015	BSP to Metric Adaptors & Reducers Ex
AB012N020E to AB004N004E and RB034N012E to RB004N312E	1 of 1	1	14 Apr 2015	BSP to NPT Adaptors & Reducers Ex
AB016B012E to AB100B004E and RB025B012E to RB100B312E	1 of 1	1	14 Apr 2015	Metric to BSP Adaptors & Reducers Ex
AB016M016E to AM100M100E and RM020M016E to RM100M090E	1 of 1	1	14 Apr 2015	Metric to Metric Adaptors & Reducers Ex
AM016N012E to AM100N004E and RM020N012E to RM100N312E	1 of 1	1	14 Apr 2015	Metric to NPT Adaptors & Reducers Ex
AN012B012E to AN004B004E and RN034B012E to RN004B312E	1 of 1	1	14 Apr 2015	NPT to BSP Adaptors & Reducers Ex
AN012M020E to AN004M100E and RN012M016E to RN004M090E	1 of 1	1	14 Apr 2015	NPT to Metric Adaptors & Reducers Ex
AN012N012E to AN004N004E and RN034N012E to RN004N312E	1 of 1	1	14 Apr 2015	NPT to NPT Adaptors & Reducers Ex
CB012B012E – CB004B004E	1 of 1	2	14 Apr 2015	Coupling BSP Male to BSP Male Ex
CB012M016E – CB004M100E	1 of 1	1	14 Apr 2015	Coupling BSP Male to Metric Male Ex
CB012N012E – CB004N004E	1 of 1	1	14 Apr 2015	Coupling BSP Male to NPT Male Ex
CM016M016E – CM100M100E	1 of 1	2	14 Apr 2015	Coupling Metric Male to Metric Male Ex

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No	Sheets	Rev	Approved date	Title
CM016N012E – CM100N004E	1 of 1	1	14 Apr 2015	Coupling Metric Male to NPT Male Ex
CN012B012E – CN004B004E	1 of 1	2	14 Apr 2015	Coupling NPT Male to BSP Male Ex
CN012N012E – CN004N004E	1 of 1	2	14 Apr 2015	Coupling NPT Male to NPT Male Ex
CN012M016E – CN004M100E	1 of 1	2	14 Apr 2015	Coupling NPT Male to Metric Male Ex
PDB012E to PDB004E	1 of 1	-	14 Apr 2015	Plug Dome Head BSP - Ex
PDM016E to PDM100E	1 of 1	2	14 Apr 2015	Ex Plugs - Metric
PHB012E – PHB004E	1 of 1	-	14 Apr 2015	Plugs Hex Head BSP - Ex
PHM016E – PHM100E	1 of 1	1	14 Apr 2015	Plugs Hex Head Metric - Ex
PHN012E – PHN004E	1 of 1	-	14 Apr 2015	Plugs Hex Head NPT - Ex
PDN012E – PDN004E	1 of 1	-	14 Apr 2015	Plugs Dome Head NPT - Ex
PSB012E – PSB004E	1 of 1	-	14 Apr 2015	Stopper Plug BSP - Ex
PSB012ER – PSB004ER				
PSM016E – PSM100E	1 of 1	1	14 Apr 2015	Stopper Plug Metric - Ex
PSM016ER – PSM100ER				
PSN012E to PSN004E	1 of 1	-	14 Apr 2015	Stopper Plug ½" NPT to 4" NPT Plug - Ex
PSN012ER to PSN004ER				
UB012B012E – UB004B004E	1 of 1	1	14 Apr 2015	Union BSP Female to BSP Female Ex
UB012N012E – UB004N004E	1 of 1	-	14 Apr 2015	Union BSP Female to NPT Female Ex
UB012M016 – UB004M100E	1 of 1	1	14 Apr 2015	Union BSP Female to Metric Female Ex
UM016M016E – UM100M100E	1 of 1	1	14 Apr 2015	Union Metric Female to Metric Female Ex
UM016M012E – UM100B004E	1 of 1	1	14 Apr 2015	Union Metric Female to BSP Female Ex
UM016M012E – UM100N004E	1 of 1	1	14 Apr 2015	Union Metric Female to NPT Female Ex
UN012B012E – UN004B004E	1 of 1	-	14 Apr 2015	Union NPT Female to BSP Female Ex
UN012N012E – UN004N004E	1 of 1	-	14 Apr 2015	Union NPT Female to NPT Female Ex
UN012M016E – UN004M100E	1 of 1	1	14 Apr 2015	Union NPT Female to Metric Female Ex

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Issue 1

Drawing No	Sheets	Rev	Approved date	Title
AM016M016E-NSA TO AM100M100E-NSA	1 of 1	-	14 Oct 2015	Metric To Metric Insulated Adaptor Ex

Issue 2

Drawing No	Sheets	Rev	Approved date	Title
AM016M016E-NSA TO AM100M100E-NSA	1 of 1	1	01 Jun 2016	Metric To Metric Insulated Adaptor Ex
AN012N012E-NSA TO AN004N004E-NSA	1 of 1	1	01 Jun 2016	NPT to NPT Insulated Adaptor Ex

Issue 3

Drawing No	Sheets	Rev	Approved date	Title
AM016M100E MARKING	1 of 1	9	10 Aug 2016	ADAPTORS-REDUCERSPLUGS, COUPLERS & UNIONS MARKING DETAIL
AB012B012E - AB004B004E and RB034B012E - RB004B312E	1 of 1	2	10 Aug 2016	BSP TO BSP ADAPTORS & REDUCERS Ex
AB012N012E - AB004N004E RB034N012E - RB004N312E	1 of 1	2	10 Aug 2016	BSP TO NPT ADAPTORS & REDUCERS Ex
CB012B012E - CB004B004E	1 of 1	3	10 Aug 2016	COUPLING BSP MALE TO BSP MALE Ex
CB012M016E - CB004M100E	1 of 1	2	10 Aug 2016	COUPLING BSP MALE TO METRIC MALE Ex
CB012N012E -CB004N004E	1 of 1	2	10 Aug 2016	COUPLING BSP MALE TO NPT MALE Ex
CM016M016E - CM100M100E	1 of 1	3	10 Aug 2016	COUPLING METRIC MALE TO METRIC MALE Ex
CM016N012E - CM100N004E	1 of 1	2	10 Aug 2016	COUPLING METRIC MALE TO NPT MALE Ex
CN012N012E - CN004N004E	1 of 1	3	10 Aug 2016	COUPLING NPT MALE TO NPT MALE Ex
AM016B012E to AM100B004E and RM025B012E to RM100B312E	1 of 1	2	10 Aug 2016	METRIC TO BSP ADAPTORS & REDUCERS Ex

Certificate Annex



Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD

Drawing No	Sheets	Rev	Approved date	Title
AM016M016E to AM100M100E and RM020M016E to RM100M090E	1 of 1	2	10 Aug 2016	METRIC TO METRIC ADAPTORS & REDUCERS Ex
AM016N012E to AM100N004E and RM020N012E to RM100N312E	1 of 1	2	10 Aug 2016	METRIC TO NPT ADAPTORS & REDUCERS Ex
AN012B012E to AN004B004E and RN034B012E to RN004B312E	1 of 1	2	10 Aug 2016	NPT TO BSP ADAPTORS & REDUCERS Ex
AN012M020E to AN004M100E and RN012M016E to RN004M090E	1 of 1	2	10 Aug 2016	NPT TO METRIC ADAPTORS & REDUCERS Ex
AN012N012E to AN004N004E and RN034N012E to RN004N312E	1 of 1	2	10 Aug 2016	NPT TO NPT ADAPTORS & REDUCERS Ex
PDB012E to PDB004E	1 of 1	1	10 Aug 2016	PLUGS DOME HEAD BSP - Ex
PDM016E to PDM100E	1 of 1	3	10 Aug 2016	EX PLUGS - METRIC
PDN012E to PDN004E	1 of 1	1	10 Aug 2016	PLUGS DOME HEAD NPT -Ex
PHB012E - PHB004E	1 of 1	1	10 Aug 2016	PLUGS HEX HEAD BSP - Ex
PHM016E - PHM100E	1 of 1	2	10 Aug 2016	PLUGS HEX HEAD METRIC - Ex
PHN012E to PHN004E	1 of 1	1	10 Aug 2016	PLUGS HEX HEAD NPT - Ex
PSB012E-PSB004E PSB012ER-PSB004ER	1 of 1	1	10 Aug 2016	STOPPER PLUG BSP - Ex
PSM016E-PSM100E PSM016ER-PSM100ER	1 of 1	2	10 Aug 2016	STOPPER PLUG METRIC - Ex
PSN012E to PSN004E PSN012ER to PSN004ER	1 of 1	1	10 Aug 2016	STOPPER PLUG 1/2" NPT TO 4" NPT PLUG Ex
UB012B012E - UB004B004E	1 of 1	2	10 Aug 2016	UNION BSP FEMALE TO BSP FEMALE Ex
UB012M016E - UB004M100E	1 of 1	2	10 Aug 2016	UNION BSP FEMALE TO METRIC FEMALE Ex
UB012N012E - UB004N004E	1 of 1	1	10 Aug 2016	UNION BSP FEMALE TO NPT FEMALE Ex
UM016B012E - UM100B004E	1 of 1	2	10 Aug 2016	UNIONS METRIC FEMALE TO BSP FEMALE Ex
UM016M016E - UM100M100E	1 of 1	6	10 Aug 2016	UNION METRIC FEMALE TO METRIC FEMALE Ex
UM016N012E - UM100N004E	1 of 1	2	10 Aug 2016	UNIONS METRIC FEMALE TO NPT FEMALE Ex
UN012B012E - UN004B004E	1 of 1	1	10 Aug 2016	UNIONS NPT FEMALE TO BSP FEMALE Ex

This certificate shall only be copied
in its entirety and without change

www.CMLEx.com

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No	Sheets	Rev	Approved date	Title
UN012M016E - UN004M100E	1 of 1	2	10 Aug 2016	UNIONS NPT FEMALE TO METRIC FEMALE Ex
PAM020M020E - PAM025M025E	1 of 1	-	10 Aug 2016	POSI ADAPTOR
AB012M020E - AB004M100E RB012M016E - RB004M100E	1 of 1	2	10 Aug 2016	BSP TO METRIC ADAPTORS & REDUCERS Ex
CN012M016E-CN004M100E	1 of 1	3	10 Aug 2016	COUPLING NPT MALE TO METRIC MALE Ex
CN012B012E -CN004B004E	1 of 1	3	10 Aug 2016	COUPLING NPT MALE TO BSP MALE Ex
UN012N012E -UN004N004E	1 of 1	1	10 Aug 2016	UNIONS NPT FEMALE TO NPT FEMALE Ex

Issue 4

No new drawings

Issue 5

Drawing No	Sheets	Rev	Approved date	Title
AM016M100E MARKING	1 of 1	10	23 Aug 2019	Adaptors-Reducers-Plugs-Couplers and Unions Marking Details
AB012B012E to AB004B004E and RB034B012E to RB004B312E	1 of 1	3	23 Aug 2019	BSP to BSP Adaptors & Reducers Ex
AB012M020E to AB004M100E and RB012M016E to RB004M100E	1 of 1	3	23 Aug 2019	BSP to Metric Adaptors & Reducers Ex
AB012N012E to AB004N004E and RB034N012E to RB004N312E	1 of 1	3	23 Aug 2019	BSP to NPT Adaptors & Reducers Ex
AM016B012E to AB100B004E and RM025B012E to RM100B312E	1 of 1	3	23 Aug 2019	Metric to BSP Adaptors & Reducers Ex
AM016M016E to AM100M100E and RM020M016E to RM100M090E	1 of 1	3	23 Aug 2019	Metric to Metric Adaptors & Reducers Ex
AM016N012E to AM100N004E and RM020N012E to RM100N312E	1 of 1	3	23 Aug 2019	Metric to NPT Adaptors & Reducers Ex

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No	Sheets	Rev	Approved date	Title
AN012B012E to AN004B004E and RN034B012E to RN004B312E	1 of 1	3	23 Aug 2019	NPT to BSP Adaptors & Reducers Ex
AN012M020E to AN004M100E and RN012M016E to RN004M090E	1 of 1	3	23 Aug 2019	NPT to Metric Adaptors & Reducers Ex
AN012N012E to AN004N004E and RN034N012E to RN004N312E	1 of 1	3	23 Aug 2019	NPT to NPT Adaptors & Reducers Ex
CB012B012E – CB004B004E	1 of 1	4	23 Aug 2019	Coupling BSP Male to BSP Male Ex
CB012M016E – CB004M100E	1 of 1	3	23 Aug 2019	Coupling BSP Male to Metric Male Ex
CB012N012E – CB004N004E	1 of 1	3	23 Aug 2019	Coupling BSP Male to NPT Male Ex
CM016M016E – CM100M100E	1 of 1	4	23 Aug 2019	Coupling Metric Male to Metric Male Ex
CM016N012E – CM100N004E	1 of 1	3	23 Aug 2019	Coupling Metric Male to NPT Male Ex
CN012B012E – CN004B004E	1 of 1	4	23 Aug 2019	Coupling NPT Male to BSP Male Ex
CN012M016E – CN004M100E	1 of 1	4	23 Aug 2019	Coupling NPT Male to Metric Male Ex
CN012N012E – CN004N004E	1 of 1	4	23 Aug 2019	Coupling NPT Male to NPT Male Ex
PAM020M020E – PAM025M025E	1 of 1	1	23 Aug 2019	POSI Adaptor
PDB012E to PDB004E	1 of 1	2	23 Aug 2019	Plug Dome Head BSP - Ex
PDM016E to PDM100E	1 of 1	4	23 Aug 2019	Ex Plugs - Metric
PDN012E – PDN004E	1 of 1	2	23 Aug 2019	Plugs Dome Head NPT - Ex
PHB012E – PHB004E	1 of 1	2	23 Aug 2019	Plugs Hex Head BSP - Ex
PHM016E – PHM100E	1 of 1	3	23 Aug 2019	Plugs Hex Head Metric - Ex
PHN012E – PHN004E	1 of 1	2	23 Aug 2019	Plugs Hex Head NPT - Ex
PSB012E – PSB004E	1 of 1	2	23 Aug 2019	Stopper Plug BSP - Ex
PSB012ER – PSB004ER				
PSM016E – PSM100E	1 of 1	3	23 Aug 2019	Stopper Plug Metric - Ex
PSM016ER – PSM100ER				
PSN012E to PSN004E	1 of 1	2	23 Aug 2019	Stopper Plug ½" NPT to 4" NPT Plug - Ex
PSN012ER to PSN004ER				

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No	Sheets	Rev	Approved date	Title
UB012B012E – UB004B004E	1 of 1	3	23 Aug 2019	Union BSP Female to BSP Female Ex
UB012M016E – UB004M100E	1 of 1	3	23 Aug 2019	Union BSP Female to Metric Female Ex
UB012N012E – UB004N004E	1 of 1	2	23 Aug 2019	Union BSP Female to NPT Female Ex
UM016M012E – UM100B004E	1 of 1	3	23 Aug 2019	Unions Metric Female to BSP Female Ex
UM016M016E – UM100M100E	1 of 1	7	23 Aug 2019	Union Metric Female to Metric Female Ex
UM016N012E – UM100N004E	1 of 1	3	23 Aug 2019	Unions Metric Female to NPT Female Ex
UN012B012E – UN004B004E	1 of 1	2	23 Aug 2019	Unions NPT Female to BSP Female Ex
UN012M016E – UN004M100E	1 of 1	3	23 Aug 2019	Union NPT Female to Metric Female Ex
UN012N012E – UN004N004E	1 of 1	2	23 Aug 2019	Union NPT Female to NPT Female Ex

Issue 6

Drawing No	Sheets	Rev	Approved date	Title
AM016M016E TO AM130M130E AND RM020M016E TO RM130M120E	1 of 1	-	28 Feb 2020	METRIC TO METRIC ADAPTORS & REDUCERS Ex
AM016N012E – AM100N004E and RM025N012E – RM130N004E	1 of 1	-	28 Feb 2020	METRIC TO NPT ADAPTORS & REDUCERS Ex
AM016B012E – AM110B004E and RM025B012E – RM130B004E	1 of 1	-	28 Feb 2020	METRIC TO BSP ADAPTORS & REDUCERS Ex
CM016M016E – CM130M130E	1 of 1	-	28 Feb 2020	COUPLING METRIC MALE TO METRIC MALE Ex
CM016N012E – CM130N004E	1 of 1	-	28 Feb 2020	COUPLING METRIC MALE TO NPT MALE Ex
CB012M016E – CB004M130E	1 of 1	-	28 Feb 2020	COUPLING BSP MALE TO METRIC MALE Ex
UM016M016E – UM130M130E	1 of 1	-	28 Feb 2020	UNION METRIC FEMALE TO METRIC FEMALE Ex
UM016N012E – UM130N004E	1 of 1	-	28 Feb 2020	UNIONS METRIC FEMALE TO NPT FEMALE Ex
UM016B012E – UM130B004E	1 of 1	-	28 Feb 2020	UNIONS METRIC FEMALE TO BSP FEMALE Ex

Certificate Annex



Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD

Drawing No	Sheets	Rev	Approved date	Title
PDM016E TO PDM130E	1 of 1	-	28 Feb 2020	DOME HEAD PLUGS- METRIC
PHM016E – PHM130E	1 of 1	-	28 Feb 2020	PLUGS HEX HEAD METRIC - Ex
PSM016E – PSM130E and PSM016ER – PSM130ER	1 of 1	-	28 Feb 2020	STOPPER PLUG METRIC - Ex
AM016M016E-NSA TO AM130M130E-NSA	1 of 1	-	28 Feb 2020	METRIC TO METRIC INSULATED ADAPTOR Ex

Issue 7

Drawing No.	Sheets	Rev	Approved date	Title
3527- PLUG	1 of 1	4	26 Jul 2022	No. "X" NON METALLIC ENCLOSURE PLUGS
AM016B012E - AM100B004E and RM025B012E - RM130B004E	1 of 1	1	26 Jul 2022	METRIC TO BSP ADAPTORS & REDUCERS Ex
AM016M016E TO AM130M130E AND RM020M016E TO RM130M120E	1 of 1	1	26 Jul 2022	METRIC TO METRIC ADAPTORS & REDUCERS Ex
AM016M016E-NSA TO AM130M130E-NSA	1 of 1	2	26 Jul 2022	AM016M016E-NSA TO AM130M130E-NSA
AM016M100E MARKING	1 of 1	12	26 Jul 2022	ADAPTORS-REDUCERS-PLUGS, COUPLERS & UNIONS MARKING DETAIL
AM016N012E - AM100N004E and RM025N012E TO RM130N004E	1 of 1	1	26 Jul 2022	METRIC TO NPT ADAPTORS & REDUCERS Ex
AM20M020E-IE TO AM100M100E-IE	1 of 1	-	26 Jul 2022	METRIC TO METRIC ADAPTORS - IE Ex
AN012N012E TO AN004N004E AND RN034N012E TO RN004N312E	1 of 1	4	26 Jul 2022	NPT TO NPT ADAPTORS & REDUCERS Ex
AN012N012E-NSA TO AN004N004E-NSA	1 of 1	3	26 Jul 2022	NPT TO NPT INSULATED ADAPTOR Ex
CB012M016E - CB004M130E	1 of 1	1	26 Jul 2022	COUPLING BSP MALE TO METRIC MALE Ex

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No.	Sheets	Rev	Approved date	Title
CM016M016E - CM130M130E	1 of 1	1	26 Jul 2022	COUPLING METRIC MALE TO METRIC MALE Ex
CM016N012E - CM130N004E	1 of 1	1	26 Jul 2022	COUPLING METRIC MALE TO NPT MALE Ex
PDM016E - PDM130E	1 of 1	1	26 Jul 2022	DOME HEAD PLUGS-METRIC
PHM016E - PHM130E	1 of 1	1	26 Jul 2022	PLUGS HEX HEAD METRIC - Ex
PSM016E - PSM130E and PSM016ER - PSM130ER	1 of 1	1	26 Jul 2022	STOPPER PLUG METRIC - Ex
UM016B012E - UM130B004E	1 of 1	1	26 Jul 2022	UNIONS METRIC FEMALE TO BSP FEMALE Ex
UM016M016E - UM130M130E	1 of 1	1	26 Jul 2022	UNION METRIC FEMALE TO METRIC FEMALE Ex
UM016N012E - UM130N004E	1 of 1	1	26 Jul 2022	UNIONS METRIC FEMALE TO NPT FEMALE Ex

Issue 8

Drawing No.	Sheets	Rev	Approved date	Title
AELB - ASSY	1 of 1	2	23 Jun 2023	ADJUSTABLE ELBOW GENERAL ASSEMBLY
AT ADAPTOR ASSY	1 of 1	2	23 Jun 2023	ADJUSTABLE T ADAPTOR ASSEMBLY
AY ADAPTOR ASSY	1 of 1	2	23 Jun 2023	ADJUSTABLE Y ADAPTOR ASSEMBLY
AELB BODY	1 of 1	-	23 Jun 2023	ADJUSTABLE ELBOW BODY
AELB NUT	1 of 1	-	23 Jun 2023	ELBOW NUT
AT BODY	1 of 1	-	23 Jun 2023	ADJUSTABLE T ADAPTOR BODY
AY BODY	1 of 1	-	23 Jun 2023	ADJUSTABLE Y ADAPTOR BODY
SWIVEL MARKING -ATEX & IECEx	1 of 1	-	23 Jun 2023	SWIVEL ADAPTOR, COUPLING, 45°, ELBOW MARKING
SWIVEL NUT	1 of 1	-	23 Jun 2023	NUT FOR SWIVEL ADAPTOR, COUPLER, 45° & ELBOW
SA-I	1 of 1	-	23 Jun 2023	SWIVEL ADAPTOR MALE

This certificate shall only be copied in its entirety and without change

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No.	Sheets	Rev	Approved date	Title
S45 FEMALE	1 of 1	-	23 Jun 2023	SWIVEL 45° FEMALE
S45 ASSY	1 of 1	-	23 Jun 2023	SWIVEL 45° ASSY
SB45 ASSY	1 of 1	-	23 Jun 2023	SWIVEL BARRIER 45° ASSY
SA FEMALE	1 of 1	-	23 Jun 2023	SWIVEL ADAPTOR FEMALE
SA ASSY	1 of 1	-	23 Jun 2023	SWIVEL ADAPTOR ASSEMBLY
SBA ASSY	1 of 1	-	23 Jun 2023	SWIVEL BARRIER ADAPTOR ASSY
SELB FEMALE	1 of 1	-	23 Jun 2023	SWIVEL ELBOW FEMALE
SELB ASSY	1 of 1	-	23 Jun 2023	SWIVEL ELBOW ASSY
SBELB ASSY	1 of 1	-	23 Jun 2023	SWIVEL BARRIER ELBOW ASSY
SC MALE	1 of 1	-	23 Jun 2023	SWIVEL COUPLER MALE
SC ASSY	1 of 1	-	23 Jun 2023	SWIVEL COUPLER ASSY
SBC ASSY	1 of 1	-	23 Jun 2023	SWIVEL BARRIER COUPLER ASSY
SBA-S	1 of 1	-	23 Jun 2023	SBA RESIN SLEEVE

Issue 9

Drawing No.	Sheets	Rev	Approved date	Title
AB012B012E to AB004B004E and RB034B012E to RB004B312E	1 of 1	4	22 Jan 2026	BSP TO BSP ADAPTORS & REDUCERS Ex
AB012M020E to AB004M100E and RB012M016E to RB004M100E	1 of 1	4	22 Jan 2026	BSP TO METRIC ADAPTORS & REDUCERS Ex
AB012N012E to AB004N004E and RB034N012E to RB004N312E	1 of 1	4	22 Jan 2026	BSP TO NPT ADAPTORS & REDUCERS Ex
AELB BODY	1 of 1	1	22 Jan 2026	ADJUSTABLE ELBOW BODY
AM016B012E - AM110B004E and RM025B012E - RM130B004E	1 of 1	2	22 Jan 2026	METRIC TO BSP ADAPTORS & REDUCERS Ex

Certificate Annex

Certificate Number **CML 15ATEX1040X**

Equipment Threaded Adaptors, Reducers, Unions, Couplers, Blanking Plugs, Insulated Adaptors, Insulated Reducers, Adjustable Elbow / 'T' / 'Y' Adaptors, Swivel Adaptors, Swivel Couplers and Swivel Elbow /45° Adaptors

Manufacturer CCG Cable Terminations PTY LTD



Drawing No.	Sheets	Rev	Approved date	Title
AM016M016E to AM130M130E and RM020M016E to RM130M120E	1 of 1	2	22 Jan 2026	METRIC TO METRIC ADAPTORS & REDUCERS Ex
AM016M016E-NSA to AM130M130E-NSA	1 of 1	3	22 Jan 2026	METRIC TO METRIC INSULATED ADAPTOR Ex
AM016N012E - AM100N004E and RM025N012E - RM130N004E	1 of 1	2	22 Jan 2026	METRIC TO NPT ADAPTORS & REDUCERS Ex
AN012B012E to AN004B004E and RN034B012E to RN004B312E	1 of 1	4	22 Jan 2026	NPT TO BSP ADAPTORS & REDUCERS Ex
AN012M020E to AN005M130E and RN012M016E to RN005M110E	1 of 1	-	22 Jan 2026	NPT TO METRIC ADAPTORS & REDUCERS Ex
AN012N012E to AN005N005E and RN034N012E to RN005N004E	1 of 1	-	22 Jan 2026	NPT TO NPT ADAPTORS & REDUCERS Ex
AN012N012E-NSA to AN004N004E-NSA	1 of 1	4	22 Jan 2026	NPT TO NPT INSULATED ADAPTOR Ex
PDM012E - PDM130E	1 of 1	-	22 Jan 2026	DOME HEAD PLUGS - METRIC
PHM012E - PHM130E	1 of 1	0	22 Jan 2026	PLUGS HEX HEAD METRIC - Ex
PSM012E - PSM130E and PSM012ER - PSM130ER	1 of 1	-	22 Jan 2026	STOPPER PLUG METRIC - Ex
SB45 ASSY	1 of 1	2	22 Jan 2026	SWIVEL BARRIER 45° ASSY
SBA ASSY	1 of 1	2	22 Jan 2026	SWIVEL BARRIER ADAPTOR ASSY
SBC ASSY	1 of 1	2	22 Jan 2026	SWIVEL BARRIER COUPLER ASSY
SBELB ASSY.	1 of 1	2	22 Jan 2026	SWIVEL BARRIER ELBOW ASSY.